


The Trends Professional Series by Vinylmax combines high quality features with industry-leading value for any new home. With an attractive brickmold frame design and a convenient J-channel structure, curb appeal is assured. Great thermal performance, lifestyle-friendly features like low maintenance exterior and a tilt-in sash, are all protected by a lifetime warranty.



STANDARD FEATURES

- **Brickmold J-Channel 2-15/16" fusion welded PVC frame and sash** provide lasting, low-maintenance beauty.
- **Integral nailing fin** is 1-1/2" long and set back 1-3/4".
- **3/4" Intercept warm-edge insulating glass** is the foundation of thermal performance and comfort.
- **BioMaxx composite sweep locks** are lead free and nest securely into the tamperproof retainer.
- **Stainless steel constant force balance system** and metal on metal pivot bar system keeps the sash aligned and moves with minimal force.
- **Integral extruded lift rail** will never pull loose for assured confidence in operation and function.
- **Sloped sill** efficiently diverts water away from the interior.
- **Full overlap interlock and mylar fin synthetic weatherstripping** at meeting rail keep out drafts.
- **Recessed tilt latches** release the sash for trouble-free cleaning of both sides of the glass.
- **Included half screen features BetterVue mesh.**
- **Non-Prorated Limited Lifetime Warranty** covers vinyl, glass, screens and hardware for as long as you live in your home and is transferable.
- **Optional IntelliGlass Low E glass** with argon gas fill heightens energy efficiency.
- **Optional reinforcement packages** for enhanced structural performance.

Optional white primed extension jambs allow the window to easily fit the depth of the opening. Available in 4-9/16" or 6-9/16" widths.



J-CHANNEL

INTEGRAL NAILING FIN

INTERCEPT SPACER

EXTENSION JAMBS


INTELLIGLASS LOW E

SIZE LIMITS

	Width	Height	UI*
Minimum	12"	22"	34
Maximum	52"	98"	150

*United Inches = Width + Height

CROSS SECTIONS



13
EXTERIOR
COLORS

ENDLESS
STYLE
OPTIONS

CHOOSE YOUR PERFECT LOOK

VINYL COLOR




White

Trends 6500 are available in white with the option to add one of 13 painted exterior finishes (below).


MATCHING STYLES



2 Lite Slider



3 Lite Sliders



Fixed




Geometrics



Patio Door

GRIDS



Colonial Perimeter

EXTERIOR FINISHES



Butter



Tan



Clay



Pebble



Silver



Terra



Cocoa



Chestnut



Chocolate



Bronze



Black



Forest



Brick



PROVEN PERFORMANCE

THERMAL

No Grids

With Grids

T6500 Single Hung	U-Value	SHGC	VLT	U-Value	SHGC	VLT
Clear Glass	.49	.65	.66	.49	.58	.59
IntelliGlass Low E / Argon	.31	.30	.54	.31	.27	.48
IntelliGlass X Low E / Argon	.30	.23	.51	.30	.21	.46

T6550/T6553 Trends Slider	U-Value	SHGC	VLT	U-Value	SHGC	VLT
Clear Glass	.48	.65	.66	.48	.58	.59
IntelliGlass Low E / Argon	.30	.30	.54	.30	.27	.48
IntelliGlass X Low E / Argon	.30	.23	.51	.30	.21	.46

T6570 Trends Picture Window	U-Value	SHGC	VLT	U-Value	SHGC	VLT
Clear Glass	.47	.67	.69	.47	.61	.62
IntelliGlass Low E / Argon	.28	.31	.56	.28	.28	.51
IntelliGlass X Low E / Argon	.28	.24	.54	.28	.22	.48

STRUCTURAL

Product Rating	Up to this size window*	Design Pressure PSF	Glass Strength	Reinforcement Configuration
Single Hung	44" x 72"	25	SS	None
	48" x 60"	30	SS	Lock and Meeting Rail
	40" x 63"	50	DS	Full
Slider	72" x 48"	30	SS	Lock and Meeting Rail
	71" x 55"	30	DS	Lock and Meeting Rail
	72" x 48"	50	DS	Full
PW	48" x 72"	50	DS	None
	60" x 84"	50	3/16"	None

83327.01-501.-47

A9904.02-116-45

The lower the **U-value**, the greater a window's resistance to heat flow and the better its insulating value.

The lower the **SHGC**, the more a product is blocking solar heat from coming through the window.

VLT - Visible Light Transmittance - lower values mean less light passing through the window.

*windows outside these size limits have not been structurally tested

vinylmax
windows

info@vinylmax.com
(800) 847-3736
www.vinylmax.com

